

1-Ton Double Layer Flat Webbing Sling with 5:1 Safety Factor

This webbing sling is made from high-tenacity polyester using advanced weaving technology. It has a 5:1 safety factor and a load range of 1 ton.



ADDITIONAL IMAGES



Product Overview

High-Tenacity Lifting Solution

This 1-ton double layer flat webbing sling is engineered from 100% high-tenacity polyester using advanced international weaving technology. Designed for professional lifting applications, it features a 5:1 safety factor and complies with EN1492 standards to ensure reliable performance in construction and manufacturing environments. The double-layer construction and folded eye design provide enhanced durability and versatile rigging options for various load types.

Technical Specifications

Working Load Limit (W.L.L.)

1 Ton

Rated Capacity

Safety Factor

5:1

Physical Dimensions

Dimension	Value
Width	25mm
Length	1m
Layer	Double Layer

Material	100% high tenacity polyester
-----------------	------------------------------

Design & Compliance

Standards	EN1492, CE, TÜV Rheinland Certified
Lifting Eye Type	Folded Eye
Color Standard	According to EN standard or as required

Manufacturing Capabilities

Customization Range

- Safety factors available: 4:1, 5:1, 6:1, 7:1, 8:1
- Load range: 0.5t to 50t
- Custom sewing methods available
- International standard color coding