

100W Outdoor LED Flood Light

This LED flood light is designed for outdoor use, providing bright and uniform illumination. Its robust housing is rated IP65 for water and dust resistance, ensuring durability.

技术参数
Technical Specifications

功率 (W)	尺寸 (mm)	重量 (kg)	照度 (lx)	光束角 (°)	色温 (K)	显色指数 (CRI)	防护等级 (IP)	输入电压 (V)	功率因数 (PF)	浪涌保护 (kV)	
RC-PB10	10W	122*71	800	80	0.9	85-265V	3000-6500K	IP65	26V	302121	4
RC-PB20	20W	143*71.5	1600	80	0.9	85-265V	3000-6500K	IP65	26V	302121	4
RC-PB30	30W	173*71.5	2400	80	0.9	85-265V	3000-6500K	IP65	26V	302121	4
RC-PB40	40W	223*71.5	3200	80	0.9	85-265V	3000-6500K	IP65	26V	302121	4
RC-PB50	50W	303*71.5	4000	80	0.9	85-265V	3000-6500K	IP65	26V	302121	4
RC-PB60	60W	373*71.5	4800	80	0.9	85-265V	3000-6500K	IP65	26V	302121	4
RC-PB80	80W	473*71.5	6400	80	0.9	85-265V	3000-6500K	IP65	26V	302121	4
RC-PB100	100W	573*71.5	8000	80	0.9	85-265V	3000-6500K	IP65	26V	302121	4
RC-PB150	150W	773*71.5	12000	80	0.9	85-265V	3000-6500K	IP65	26V	302121	4
RC-PB200	200W	973*71.5	16000	80	0.9	85-265V	3000-6500K	IP65	26V	302121	4

ADDITIONAL IMAGES



Overview

High-Performance Outdoor Illumination

This high-performance LED flood light is engineered for reliable outdoor use, featuring a robust housing with an IP65 rating for superior water and dust resistance. It delivers bright, uniform illumination, making it an ideal choice for diverse applications such as security lighting, landscape enhancement, and general area lighting. Designed for efficiency and durability, this series offers versatility with power options ranging from 10W to 200W to suit various project requirements.

Technical Specifications

Ingress Protection

IP65

Rated Power	100 W
Luminous Flux	8000 LM
Input Voltage Range	85-265V
Color Temperature	3000-6500K
Color Rendering Index (CRI)	80
Power Factor (PF)	0.9
Anti-Surge Protection	2KV

Product Range

Series Specifications Table

Model	Power	Luminous Flux	PF
RC-PB010	10W	800	0.5
RC-PB030	30W	2400	0.5
RC-PB050	50W	4000	0.5
RC-PB100	100W	8000	0.9
RC-PB200	200W	16000	0.9