

12V 5Ah Motorcycle Gel Battery

This 12V 5Ah motorcycle battery is injected with gel electrolyte for increased capacity and a longer service life. The maintenance-free design features a lead-calcium grid alloy for minimal water loss and a low self-discharge rate.



ADDITIONAL IMAGES



Product Overview

High-Performance Gel Battery

This 12V 5Ah motorcycle gel battery is engineered for reliable starting power and long-term durability. Featuring a factory-sealed, non-spillable design, it eliminates the need for initial acid filling, ensuring convenient and immediate use. The advanced gel electrolyte construction provides stable performance across a wide temperature range, making it an ideal choice for demanding motorcycle applications.

Technical Specifications

Electrical Metrics

12 V

Voltage

5 Ah

Capacity

65 CCA

Cold Cranking Amps

Charging & Maintenance

Charging Guidelines

Parameter	Specification
Standard Charge	0.5A for 5-10 hours
Rapid Charge	5.0A for 30 minutes
Charge Voltage	13.8V - 15.0V

Features & Benefits

Construction Details

- Pb-Ca grid alloy for low water loss
- Injected with Gel electrolyte
- Intelligent capacity detection

Key Features

Maintenance Free, Non-Spillable, Factory Sealed, Low Self-Discharge, Pre-Delivery Inspected

Operating Temperature Range

-30°C to 55°C