

12V Battery Charger and Starter for GEL AGM MF VRLA PbWet PbCa Batteries

This battery charger and starter is a versatile device designed for charging and starting various types of 12V batteries. It supports battery capacities from 5-200 Ah and is compatible with GEL, AGM, MF, VRLA, PbWet, and PbCa batteries.



Product Overview

Versatile Battery Management Solution

This 12V battery charger and engine starter is designed to support a wide range of battery chemistries, including GEL, AGM, MF, VRLA, PbWet, and PbCa. It features three distinct operating modes: a 2 Amp trickle charge for maintenance, a 12 Amp quick charge for rapid replenishment, and a 75 Amp jump start mode for emergencies. The unit includes intelligent status monitoring via an LED display and safety features such as a self-resetting circuit breaker and spark-proof design.

Technical Specifications

Charging Modes

2 A Trickle Charge	12 A Quick Charge	75 A Jump Start
------------------------------	-----------------------------	---------------------------

Electrical Requirements

- Input: AC 230V ~ 50 Hz
- Max Power Consumption: 240W
- Output Voltage: 12V
- Supported Capacity: 5-200 Ah

Compatible Battery Types

GEL, AGM, MF, VRLA, PbWet, PbCa

Safety & Compliance

Certifications

CE • RoHS

Safety Features

- Self-resetting circuit breaker
- Spark-proof design
- Automatic trickle switch

Logistics

Logistics & Packaging

Metric	Value
Unit Packaging Weight	6.37 kg
Carton Quantity	2 units
Carton Dimensions	54 x 28.5 x 19 cm
Carton Weight	11/12 kg
Pallet Quantity (EUR)	108 units

Container Loading Capacity

Container Type	Capacity
20' Container	1850
40' Container	2000
40' HC Container	2300