

35L Dispersion Kneader

The 35L dispersion kneader features an advanced design and imported core components. It excels in sealing, safety, abrasion resistance, stability, and precise temperature control for bulk production.



ADDITIONAL IMAGES



Product Overview

Industrial Dispersion Kneader

The 35L Dispersion Kneader utilizes advanced international design principles to deliver superior mixing performance for natural rubber, synthetic rubber, and modified plastics. Engineered for durability, the chamber features a specialized abrasion-resistant coating that significantly extends service life compared to traditional models. With precise temperature control and high-torsion drive systems, this machine ensures consistent, efficient production for demanding industrial applications.

Technical Specifications

Mixing Capacity

35 L

Mixing Capacity

60 KG/load

Max Productivity

Motor Power Ratings

Component	Power Rating
Driving Motor	55
Tilting Motor	2.2
Electric Heater	10

Dimensions & Weight

- Dimensions (H x W x L): 3,200 x 1,900 x 3,000 mm
- Weight: 6,500 KG
- Tilting Angle: 140°

Features & Construction

Operational Advantages

High Abrasion Resistance • Low Noise Operation • Energy Efficient • Easy Maintenance

Engineering Highlights

Chromium-coated Chamber, 42 Cr-Mo Gear Reducer, Hardened Tooth Surface, Dry Mechanical Shaft Seal, Reverse Rotation Discharge