

# 5T x 8M Flat Webbing Sling with 7:1 Safety Factor

This webbing sling is made from high-quality synthetic fiber using advanced weaving technology. It has a 7:1 safety factor and a load range from 0.5t to 50t.



## ADDITIONAL IMAGES



## Overview

### High-Performance Flat Webbing Sling

This high-strength flat webbing sling is engineered for demanding industrial lifting applications, featuring a robust 7:1 safety factor for enhanced operational security. Constructed from 100% high-tenacity polyester, it offers excellent durability and resistance to abrasion. Designed to meet international safety standards, this versatile tool ensures reliable performance for heavy-duty lifting tasks in various environments.

## Technical Specifications

### Safety Factor

7:1

### Working Load Limit (WLL)

**5 Ton**

Working Load Limit

### Layer Configuration

- Single ply
- Double ply
- Four ply

### Material

100% High Tenacity Polyester

### Compliance Standard

EN1492

## Dimensions & Customization

Length	8 m
Width Range	25-300mm
Customization	Yes

## Lifting Eye Types

### Available Eye Configurations

Type
Flat Eye
Reversed Eye
Folded Eye 1/2 Width from 1 Side
Folded Eye 1/2 Width from 2 Sides
Folded Eye 1/3 Width