

# 60A 3-Pole AC Magnetic Contactor

This 3-pole magnetic contactor is rated for 60A and up to 600V. It is suitable for switching resistive and inductive loads in HVAC systems.



## ADDITIONAL IMAGES



## Product Overview

### Professional HVAC Magnetic Contactor

This 3-pole magnetic contactor is engineered for reliable performance in demanding HVAC and refrigeration applications. It supports both single-phase and 3-phase systems, offering a robust solution for switching inductive and resistive loads. With CUL certification and a design optimized for hermetic compressors, this unit ensures safety and durability in commercial and residential electrical systems.

## Electrical Ratings

### Rated Current

**60 A**

Full Load Amps (FLA)

**75 A**

Resistive Load

Maximum Voltage	600 V
Coil Voltage	24VAC 50/60 Hz
Pole Configuration	3
System Compatibility	1-Phase, 3-Phase

## Installation & Torque

### Torque Specifications (Copper Conductors @ 75°C)

Component	Torque
Screws	22 in-lbs
Lugs	50 in-lbs

## Compliance & Quality

### Certifications

CUL Certified

### Quality Assurance

- 100% self-inspection
- Pre-packing testing

## Ordering Information

### Delivery Time

15-20 days after deposit

### Payment Terms

30% deposit, balance against B/L copy