

Automatic Desiccant Packet Filling Machine

This automatic granular packaging machine is designed for filling non-sticky, bulk materials. It is suitable for producing desiccant packets using materials like silica gel.



ADDITIONAL IMAGES



Product Overview

Automated Desiccant Packaging Solution

This automatic granular packaging machine is designed for high-efficiency production of desiccant packets and similar non-sticky, bulk materials. The system integrates bag making, measuring, filling, sealing, cutting, and coding into a single continuous process. Engineered for 24-hour operation, it offers high-speed performance and precise accuracy for demanding industrial packaging environments.

Performance Metrics

Packaging Speed

100 bags/min
Max Speed

50 bags/min
Min Speed

Filling Accuracy

3 %

Technical Specifications

Measurement Range

1-40ml

Sealing Method

Three-side sealing

Bag Dimensions

Bag Size Range

Dimension	Range
Length	55-110mm
Width	30-80mm

Compatibility & Materials

Compatible Packing Materials	PET/plated AL/PE, PET/PE, NYLON
------------------------------	---------------------------------

Physical Attributes

Machine Dimensions	600 x 790 x 1780 mm
Total Weight	350 kg

Electrical Requirements

- Power Requirements
- Voltage: 220V
 - Frequency: 50HZ
 - Power Consumption: 1.5KW