

# Ceramic Lined Composite Pipe and Elbow

Ceramic lined composite pipes and elbows are designed for pneumatic and pumping conveying of powders. These composite parts include elbows, short sections, tee joints, and reducers.



## ADDITIONAL IMAGES



## Product Overview

### Industrial Ceramic Lined Composite Piping

These ceramic lined composite pipes and elbows are engineered for high-performance pneumatic and pumping conveying systems. By combining the structural integrity of steel with the extreme hardness and wear resistance of ceramic liners, these components significantly extend operational lifespan in harsh environments. They feature a smooth inner wall to prevent clogging, making them ideal for high-speed, abrasive material transport.

## Technical Specifications

### Connection Type

Flange • Welding

Flange Standards	ASME B16.5, GB/T9113
------------------	----------------------

Nominal Pressure	1 MPa
------------------	-------

Pressure Class	Class150
----------------	----------

Size Range (Metric)	DN50 ~ DN300
---------------------	--------------

Size Range (Imperial)	NPS2 ~ NPS12
-----------------------	--------------

Max Working Temperature	200
-------------------------	-----

## Materials

### Composition

- Engineering Ceramic
- Steel

## Applications

### Primary Applications

Industry	Application
Power Plants	Slag draining, ash removal, powder feeding
Steel Plants	Iron alloy conveying, slag conveying, external refining
Cement Plants	LiCoO <sub>2</sub> powder, raw slurry conveying, coal powder
Construction	Concrete conveying