

Diaphragm Pump Airless Paint Sprayer

This airless paint sprayer utilizes a diaphragm pump for consistent, high-pressure paint delivery. It is suitable for various applications, offering adjustable pressure settings and durable construction.



Overview

Professional Airless Paint Sprayer

This diaphragm pump airless paint sprayer is designed for high-efficiency painting on small to medium-scale projects. Featuring a robust cart-mounted design with pneumatic wheels, it offers excellent portability and maneuverability on job sites. The system includes a reliable mechanical pressure control valve and high-quality stainless steel/tungsten carbide valves to ensure consistent, professional-grade performance.

Performance Metrics

Max Flow Rate

2.1 L/min
Max Flow

0.55 gpm
Max Flow

Motor Power	1150 W
Maximum Pressure	210 Bar

Technical Specifications

Nozzle Specifications

Metric	Value
Suggested Nozzle	0.017"
Maximum Nozzle	0.019"
Optimal Distance	350-400mm

Model Number	SPX1150-210
Voltage/Frequency	110/220V, 50/60Hz
Hydraulic Oil Type	ISO VG32

Logistics & Compliance

Product Weights

- Net Weight: 29kg
- Gross Weight: 31kg

Certifications	EMC, LVD, MD, RoHS, GS
Packing Size	52 x 45 x 64 cm

Standard Accessories

Included Accessories

- 15m pressure hose
- 60cm extension wand
- Spray gun with tip 517
- Hand tool kit
- Suction tube
- Pressure gauge
- Easy wearing spare parts
- English manual