

# Ductile Iron Double Socket Bend

This ductile iron double socket bend facilitates directional changes in piping systems. It features sockets for secure pipe connections and a protective coating.



## Product Overview

### High-Performance Ductile Iron Fittings

These ductile iron double socket bends are designed for high-pressure water processing and sewage systems, offering exceptional durability and corrosion resistance. Available in a wide range of diameters from DN80 to DN2600mm, they provide versatile solutions for large-scale municipal and industrial pipeline engineering. Each component is manufactured to meet rigorous international quality standards, ensuring long-term reliability in diverse environmental conditions.

### Primary Applications

- Water Processing Engineering
- Sewage Systems
- Water Conservancy Projects
- Municipal Pipelines

## Technical Specifications

### Diameter Range

**80 mm**

Min DN

**2600 mm**

Max DN

### Available Pipe Lengths

- 6 meters
- 8.15 meters

### Material

Ductile Iron

### Connection Type

Double Socket

## Quality & Compliance

### Management Systems

- Occupational Health and Safety Management System
- Environmental Management System
- Quality Management System

### Quality Certifications

ISO 9001, ISO 14001, GB/T28001, French BV, Korea KS

## Supply & Logistics

### Global Distribution

120 Countries • CIS Region • Global Export

Annual Production Capacity

38000 km