

# Gasoline Engine Water Pump

This self-priming centrifugal water pump is powered by a gasoline engine. It is designed for irrigation, dewatering, and general water transfer.



## ADDITIONAL IMAGES



## Overview

### High-Performance Gasoline Water Pump

This self-priming centrifugal gasoline water pump is engineered for superior durability and high-performance operation. Designed for demanding applications such as agricultural irrigation and municipal sewage projects, it features a reliable four-stroke OHV engine. With a robust protective frame and efficient design, it offers a consistent flow rate for professional water transfer needs.

## Performance Metrics

### Key Performance Indicators

**30 m<sup>3</sup>/h**

Max Flow Rate

**28 m**

Total Lift

**8 m**

Suction Lift

**3600 RPM**

Rotation Speed

## Engine Specifications

### Engine Technical Data

Parameter	Value
Model	GX200
Displacement	163 cm <sup>3</sup>
Max Output	6.5 HP
Type	One-Cylinder, Air-Cooling, Four-Stroke OHV

## Technical Specifications

### Physical Dimensions & Capacities

- Inlet/Outlet Diameter: 50mm (2 inch)
- Gasoline Tank Capacity: 3.6 L
- Machine Oil Capacity: 0.6 L
- Gross/Net Weight: 27/25 kg
- Packing Dimensions: 49 x 38.5 x 46 cm

## Features

### Key Features

Recoil Start, Low Noise Muffler, Self-Priming, High-Quality Carburetor, Cast Iron Cam Shaft Option

## Logistics

### Shipping Information

350 Sets per 20' FCL