

Rotary Gear Oil Transfer Pump

This rotary gear oil pump is designed for dispensing or transferring low viscosity and non-corrosive petroleum-based fluids. It has a maximum viscosity rating of 500 SSU (or SAE 30) and a flow rate of 1 L/stroke.



Product Overview

Professional Rotary Gear Oil Transfer Pump

This rotary gear type oil transfer pump is engineered for efficient dispensing of low-viscosity, non-corrosive petroleum fluids. Constructed from durable alloy cast aluminum, steel, NBR, and PE, it is suitable for handling petrol, diesel, kerosene, lube, fuel, and machine oil. The versatile design features a modular inlet tube that can be adjusted into 2 or 3 sections to accommodate various container depths.

Performance Metrics

Flow Rate

1 L/Stroke
Flow Rate

Maximum Viscosity: 500 SSU (or SAE 30)

Technical Specifications

Tube Dimensions

Component	Specification
Inlet Tube	1 1/4" x 40"
Outlet Tube	1"

Pump Type	Rotary-Gear
Construction Materials	Alloy Cast Aluminum, Steel, NBR, PE
Bung Adaptor	2 inch

Logistics & Packaging

Packaging Details

- Quantity: 4 PCS/CTN
- Gross Weight: 24.5 KGS
- Net Weight: 23.0 KGS
- Dimensions: 103 x 33 x 21 CM