

Scissor Lift Solid Tire

This solid tire is designed for scissor lifts, providing stability and durability. It features a non-marking compound and reinforced steel ring.



ADDITIONAL IMAGES



Product Overview

Professional Scissor Lift Solid Tires

These professional-grade solid tires are engineered specifically for aerial work platforms and scissor lifts. Constructed from high-quality natural rubber with specialized non-marking compounds, they offer superior stability and durability in demanding industrial environments. High-tech bonding processes ensure a secure, long-lasting fit between the rubber and the reinforced steel ring.

Technical Specifications



Precision-engineered tread patterns optimized for traction and surface maneuverability.

Available Sizes

| Size (Inch) | Pattern | Load @ 10km/h (kg) |
|-------------|-------------------|--------------------|
| 22x6x16 | TP328 | 2265 |
| 22x6x17 3/4 | TP328 | 2185 |
| 22x7x17 3/4 | TP305/TP321 | 4220 |
| 4.00-8 | TP303 | 1055 |
| 15x5 | TP305 | 1275 |
| 16x5 | TP303/TP329/TP328 | 1400 |
| 12x4 | TP323/TP305 | 550 |
| 600x190 | TP303/TP328 | 3360 |

Compatibility

Genie, JLG, Skyjack, Haulotte, Snorkel, XCMG, LIUGONG, Mantall

Product Features



Puncture-proof solid rubber construction designed for heavy-duty stability.

Key Features

- High-quality natural rubber compound
- Non-marking formulation for floor protection
- Reinforced steel ring construction
- High-tech adhesive bond for structural integrity
- Engineered for both indoor and outdoor utility

Performance Standards

Puncture Proof • High Load Capacity • Wear Resistant • Non-Marking