

Semiautomatic Sleeve Sealing Equipment

This semiautomatic machine utilizes a tunnel for automated sleeve sealing. It is used to shrink package single and multiple products.



ADDITIONAL IMAGES



Overview

Semiautomatic Sleeve Sealing Equipment

This semiautomatic sleeve sealing machine is designed to provide efficient and reliable packaging for a variety of single or multiple products. The system integrates a conveyor and a heat shrink tunnel to ensure high-quality, secure seals, making it an ideal choice for industries such as printing, pharmaceuticals, beverages, and industrial components. Engineered for flexibility and durability, this equipment is compatible with PE films and provides adjustable parameters to suit specific production requirements.

Key Features

Application Industries

Printing, Pharmacy, Floor, Chinaware, Beverage, Beer

Technical Specifications

Key Performance Indicators

8 pcs/min

Min Packing Speed

10 pcs/min

Max Packing Speed

18.5 kW

Power Consumption

520 kg

Net Weight

Physical Dimensions

Parameter	Size (mm)
Max Packing Size	520 × 320 × 350
Tunnel Size	1500 × 600 × 400
External Dimension	3500 × 860 × 2000

Operational Settings

Film Specifications

- Material: PE film
- Max film width: 600mm
- Suitable thickness: 40-80µm

Sealing Control

- Temperature setting: 150-250
- Sealing time: 1.5-3 seconds
- Compressed air requirement: 60 Lt/min