

Surface Mounted LED Downlight

This surface-mounted slim downlight features a die-cast aluminum construction. Its sleek design and minimal profile make it suitable for various indoor lighting applications.



Product Overview

Professional Surface Mounted LED Downlight

This high-performance surface mounted LED downlight features premium components for reliable, long-term illumination. Engineered with a special design to prevent light leakage, it offers a clean, uniform output perfect for residential, office, and hospitality environments. The fixture is designed for easy installation and low-maintenance operation, providing an energy-efficient solution for diverse interior lighting needs.

Technical Specifications

Performance Metrics

120 ° Beam Angle	25000 hrs Lifespan	80 e CRI
----------------------------	------------------------------	--------------------

Power Options	6W, 12W, 18W, 24W
Color Temperature	3000K, 4000K, 6500K
Dimmable	No
Voltage	100-240V

Model Variants

Model Specifications

Item Number	Watts	Flux	Dimensions (mm)
L-DL-0011-6W	6W	330lm	120*35
L-DL-0011-12W	12W	780lm	170*35
L-DL-0011-18W	18W	1250lm	225*35
L-DL-0011-24W	24W	1680lm	300*35
L-DL-0021-6W	6W	330lm	122*122*35
L-DL-0021-12W	12W	780lm	173*173*35
L-DL-0021-18W	18W	1250lm	227*227*35
L-DL-0021-24W	24W	1680lm	300*300*35

Applications

Recommended Use

- Residential/Home
- Office
- Restaurant
- Hotel
- Supermarket