


Two-Gang Two-Way Light Switch


This two-gang, two-way light switch controls two separate lights from two locations. It features a fire-resistant PC housing and offers options for screw or screw-less terminal connections.



ADDITIONAL IMAGES



Overview



Modular design featuring two individual switch plates within a unified frame.

Premium Modular Lighting Control

This S81 Series two-gang, two-way light switch offers a sophisticated and flexible solution for modern electrical installations. Featuring a unique 4-degree button swing angle for an elegant aesthetic, it utilizes a pendulum structure for rapid circuit switching. The modular design allows for extensive customization with various cover materials and easy inventory management for professional contractors.

Technical Performance



Back view showing terminal ports and robust PC housing construction.

Electrical Specifications

250 V

Rated Voltage


10 AX

Rated Current

Safety & Durability

- Fire resistant PC back-housing
- Withstands 850°C glow wire test
- 3000V high voltage insulation test
- Integrated child-proof shutters
- 10-year mechanical warranty

Design & Materials



Flexible combination system allows for easy inventory management and customization.

Design Features

- 4-degree elegant swing angle
- Flat and cambered design options
- Up to 27 color options
- Modular fitting for free combination

Available Cover Materials

Plastic, Wood, Glass, Aluminum, Fire-resistant PC

Installation



Clean, modern aesthetic suitable for residential and commercial flush mounting.

Installation Features

- Screw and screw-less terminal options
- Hanger installation (removable hanger option)
- Notched pins for perfect finish on uneven walls
- Universal frame for horizontal/vertical mounting

Dimensions

Mounting Standards

| Type | Hole Spacing | Total Width |
|----------------------|--------------|-------------|
| Square Mounting | 53mm | 60mm |
| Rectangular Mounting | 71mm | 124mm |

Unit Dimensions 74.7 x 74.7 x 35.2 mm

Logistics

Packaging Details

- 1 pc per bag
- 10 pcs per box
- 100 pcs per carton

Ordering Terms

- Minimum Order Quantity: 3000 PCS
- Payment Term: FOB SHUNDE

Compliance

Certifications

CE • TUV