

0.75KW Gasoline Generator

This gasoline generator provides a reliable power output for various applications. Featuring a 2HP 2-stroke engine, it is engineered with safety features and a user-friendly interface.

| |
|---|
| KJ950A |
| Type: Brushless, Revolving Magnetic Field, Self-exciting, 2 Poles, Single-phase |
| Frame: 612mm Steel Tube |
| Rated AC Output: 0.65KW |
| Max AC Output: 0.75 KW |
| Frequency: 50Hz |
| Voltage: 220~240V |
| Voltage Regulator: Condenser |
| Power Factor: Cosφ = 1.0 |
| Engine |
| Model: 1E43F 2.0HP |
| Type: Forced Air-cooled, 2-Stroke, single cylinder, Reed Valve |
| Bore × Stroke: 42mm × 42mm |
| Displacement: 63ml |
| Recommended Fuel: Unleaded Gasoline |
| Fuel tank capacity: 4.2L |
| Fuel consumption: 554g/KWhour |
| Engine Oil Capacity: Gasoline and Oil mixing ratio 40:1 |
| Start Mode: Recoil and hand-operated |
| Standard Features |
| Oil Alert: without |
| Fuel Gauge: without |
| AC Voltmeter: without |
| Indicator Light: with |
| AC Circuit Breaker: with |
| Electric Starter: without |
| Option |
| DC output(12V/8.3A): with |
| DC Circuit Breaker: with |
| Frame Pallet: with |
| Battery(12V 4.5Ah): without |
| Handle: without |
| Wheel: without |

ADDITIONAL IMAGES



Overview

Compact Power Solution

The KJ950A is a compact and robust gasoline generator engineered for reliable performance in both residential and commercial settings. Featuring a 2HP 2-stroke engine, this unit is ideal for emergency backup power, outdoor recreational activities, and running small tools or appliances. Its user-friendly interface and durable steel tube frame ensure ease of operation and long-lasting utility.

Key Performance Metrics

0.75 KW

Max AC Output

0.65 KW

Rated AC Output

2 HP

Engine Power

Electrical Specifications

Electrical Technical Details

| Parameter | Value |
|-------------------|--------------|
| Voltage | 220~240V |
| Frequency | 50Hz |
| Power Factor | 1.0 |
| Voltage Regulator | Condenser |
| Phase | Single-phase |

Engine Specifications

Engine Configuration

- Model: 1E45F
- Type: Forced air-cooled, 2-stroke, single cylinder
- Displacement: 63ml
- Bore x Stroke: 45mm x 42mm
- Start Mode: Recoil and hand-operated

Fuel and Operation

Fuel & Consumption

- Fuel Type: Unleaded Gasoline
- Mixing Ratio: 40:1 (Gasoline to Oil)
- Tank Capacity: 4.2L
- Fuel Consumption: d544g/KW-hour

Features and Options

Standard Features

Indicator Light • AC Circuit Breaker • Steel Tube Frame (112mm)

Available Options

DC Socket (12V/8.3A), DC Circuit Breaker, Foam Packing

Certifications

CE