

1-Ton Polyester Webbing Sling with Eyes

This 1-ton webbing sling is constructed from high-strength polyester. It features reinforced eye loops at both ends for secure attachment to lifting equipment.



ADDITIONAL IMAGES



Overview

High-Strength Polyester Webbing Sling

This 1-Ton polyester webbing sling is engineered for professional lifting and rigging applications, featuring a durable eye-to-eye design for versatile connection options. Constructed from 100% high-strength polyester, it provides excellent resistance to abrasion and low elongation under load. Certified to CE and GS standards, this sling ensures high safety and reliability for industrial and construction environments.

Key Features

Available Safety Factors

5:1 • 6:1 • 7:1

Safety Certifications

CE, GS, TÜV Rheinland Certified

Material

100% Polyester

Technical Specifications

Working Load Limit

1000 kg
WLL

Sling Dimensions

- Thickness: 7.5 mm
- Minimum Length: 0.5 m
- Maximum Length: 100 m

Product Range

Model Specifications Table

Type	WLL (KG)	Width (MM)	Weight (KG/M) 5:1
LiftHZBD-02	2000	25	0.38
LiftHZBD-04	4000	50	0.68
LiftHZBD-06	6000	75	1.28
LiftHZBD-08	8000	100	1.61
LiftHZBD-10	10000	125	2.04
LiftHZBD-12	12000	150	2.32
LiftHZBD-16	16000	200	3.3
LiftHZBD-20	20000	250	4.62