

100W Outdoor LED Flood Light

This LED flood light is designed for outdoor use, providing bright and uniform illumination. Its robust housing is rated IP65 for water and dust resistance, ensuring durability.

技术参数
Technical Specifications

型号	功率	尺寸	重量	光束角	色温	显色指数	防护等级	输入电压	输入功率	效率	寿命
RC-FR10	10W	122*71	80	30	0.9	80-265V	3000-6500K	IP65	20V	35.74*1045	25
RC-FR20	20W	143*71.5	100	30	0.9	80-265V	3000-6500K	IP65	20V	35.74*1045	25
RC-FR30	30W	173*71.5	120	30	0.9	80-265V	3000-6500K	IP65	20V	35.74*1045	10
RC-FR50	50W	223*71.5	150	30	0.9	80-265V	3000-6500K	IP65	20V	41.92*1250	10
RC-FR100	100W	309*71.5	200	30	0.9	80-265V	3000-6500K	IP65	20V	37.0*121	4
RC-FR150	150W	347*72	250	30	0.9	80-265V	3000-6500K	IP65	20V	37.0*121	4
RC-FR200	200W	474*71.5	300	30	0.9	80-265V	3000-6500K	IP65	20V	41.92*1250	4

ADDITIONAL IMAGES



Overview

High-Performance Outdoor Illumination

This high-performance LED flood light is engineered for reliable outdoor use, featuring a robust housing with an IP65 rating for superior water and dust resistance. It delivers bright, uniform illumination, making it an ideal choice for diverse applications such as security lighting, landscape enhancement, and general area lighting. Designed for efficiency and durability, this series offers versatility with power options ranging from 10W to 200W to suit various project requirements.

Technical Specifications

Ingress Protection

IP65

Rated Power	100 W
Luminous Flux	8000 LM
Input Voltage Range	85-265V
Color Temperature	3000-6500K
Color Rendering Index (CRI)	80
Power Factor (PF)	0.9
Anti-Surge Protection	2KV

Product Range

Series Specifications Table

Model	Power	Luminous Flux	PF
RC-PB010	10W	800	0.5
RC-PB030	30W	2400	0.5
RC-PB050	50W	4000	0.5
RC-PB100	100W	8000	0.9
RC-PB200	200W	16000	0.9