

# 10AX 3-Gang One-Way Wall Switch with Hanger

This 10AX wall switch features a three-gang, one-way configuration. It is constructed from fire-resistant PC material and has an optional removable hanger.



## Overview

### Modern 3-Gang Wall Switch

This 10AX 3-gang one-way wall switch features a classic, simple design with a large push-button interface for an elegant and noble feel. Built with fire-resistant PC material capable of withstanding 850 , it ensures high safety standards for residential and commercial environments. The modular fitting design allows for flexible combinations, while the optional hanger provides versatile installation choices to meet specific project needs.

## Technical Specifications

### Electrical Ratings

**10 AX**

Rated Current

**250 V~**

Rated Voltage

**60 Hz**

Max Frequency

Network Frequency	50/60Hz
Switch Function	3 Gang 1 Way (Mechanism supports 2 way)

## Design & Construction

Construction Materials	Fire-resistant PC, TPE, Brass, K200 Silver Contacts
Surface Finish	Glossy Button / Matt Enclosure
Actuator	Rocker

## Installation

### Mounting & Wiring

- Surface mounting
- Screw terminal fixing
- Removable hanger option
- 10mm wire stripping length
- 1.5-2.5mm<sup>2</sup> rigid wire capacity

Dimensions (with Hanger)	86 x 86 x 45 mm
--------------------------	-----------------

## Durability & Safety


### Safety Tests

- 850 Fire resistance test
- 2000V Dielectric Strength test
- >3mm Opening distance


### Service Life

40000 Cycles

## Compliance & Applications



Compliance with Low Voltage Directive 2014/35/EU for electrical safety.



TUV SUD certified rocker switches ensuring international quality standards.

### Certifications

CE • TUV • ISO 9001 • ISO 14001

### Recommended Use

Residential, Hotel, School, Bar, Exhibition Centers