

12V 5Ah Motorcycle Battery with Intelligent Detection

This 12V 5Ah motorcycle battery has a built-in electronic chip for real-time capacity monitoring. The maintenance-free design features a lead-calcium grid alloy and gel electrolyte for enhanced performance in a wide range of temperatures.



ADDITIONAL IMAGES



Product Overview

Intelligent Motorcycle Battery Technology

This 12V 5Ah motorcycle battery features an exclusive patented design with a built-in electronic chip for real-time capacity monitoring. Engineered for reliability, it utilizes advanced Pb-Ca grid alloy to minimize water loss and includes Gel electrolyte for extended service life. The factory-sealed, maintenance-free construction ensures excellent performance across a wide temperature range from -30°C to 55°C.

Technical Specifications

Voltage	12 V
Capacity	5 Ah
Cold Cranking Amps (CCA)	65 A
Operating Temperature	-30°C to 55°C

Charging Parameters

Standard Charge	0.5A for 5-10 hours
Rapid Charge	5.0A for 30 minutes
Charge Voltage Range	13.8V - 15.0V

Features

Key Features

Intelligent Detection • Maintenance Free • Non-Spillable • Factory Sealed • Gel Electrolyte

Construction Details

- Pb-Ca grid alloy for low water loss
- Built-in electronic chip for capacity monitoring
- Pre-delivery inspection guaranteed