

13A Universal Power Outlet


This 13A universal power outlet is designed to accommodate various plug types. It is suitable for residential, commercial, and industrial applications requiring a versatile and reliable power connection point.



ADDITIONAL IMAGES



Overview



The modular design allows for flexible combinations and easy inventory management for various electrical installations.

Versatile S80 Series Power Solution

The S80/13W is a high-quality 13A universal power outlet designed for international compatibility and modular flexibility. Featuring a robust earthed metal frame and flame-retardant PC back housing, it ensures a safe and stable installation even on uneven walls. This complete 1-module unit is ideal for residential and commercial applications where reliable, multi-standard power connectivity is required.

Electrical Specifications

Rated Current

13 A

Rated Current

Operating Parameters

Parameter	Value
Rated Voltage	250V~
Frequency	50-60Hz
Poles Configuration	2P + E
Outlet Standard	Schuko / Universal
Ground Lug Position	Straight 0°

Safety & Protection

Safety Protection Systems

- Short-circuit protection
- Thermal protection
- Automatic overload protection
- Child-proof safety shutters
- Battery charge protection
- Automatic restart after ground fault

Compliance & Certifications


ROHS, CE, CB, TUV, VDE, SASO, GCC

Design & Materials


Construction Materials

Component	Specification
Back-housing	Grey flame retardant PC (850°C resistant)
Mounting Frame	Earthed metal frame
Surface Finish	Glossy
Surface Treatment	Untreated or Painted options

Installation



Optional surface mounting boxes provide a flexible solution when flush-mounting is not possible.



Detailed technical measurements for precise mounting and installation planning.

Mounting & Wiring

- Fixing mode: By screws and claws
- Terminals: Screwless terminals for fast wiring (Screw optional)
- Modular fitting design for free combination
- Notched pins on frame for perfect fit on uneven walls
- Removable hanger installation option

Physical Dimensions


Dimension	Measurement (mm)
Width	82
Height	82
Total Depth	42.4
Projection Depth	13.5
Mounting Distance	60

Environmental

Temperature Limits

Condition	Range (°C)
Operation	-5 to 40 °C
Storage	-20 to 60 °C

Customization



Frames are available from 1-gang to 5-gang in up to 27 different colors, supporting both horizontal and vertical mounting.

Available Finishes

White • Black • Dark Gray • Cream • Silver • Champagne • Rose Gold