

# 150W Outdoor LED Flood Light

This LED flood light provides bright and uniform light distribution for outdoor use. It features a robust construction, making it suitable for security and landscape lighting.

Technical Specifications

型号	功率	产品尺寸	重量	光束角	色温	输入电压	防护等级	使用寿命	认证
KL-S2000	30W	181*174	650g	80°	6500K	100-265V	IP65	50,000Hrs	CE, RoHS, SGS, TUV, EMC
KL-S2000	30W	181*174	650g	80°	5000K	100-265V	IP65	50,000Hrs	CE, RoHS, SGS, TUV, EMC
KL-S2000	30W	227*187.4	650g	80°	6500K	100-265V	IP65	50,000Hrs	CE, RoHS, SGS, TUV, EMC
KL-S2000	30W	227*187.4	650g	80°	5000K	100-265V	IP65	50,000Hrs	CE, RoHS, SGS, TUV, EMC
KL-S2000	100W	273*203.74	650g	80°	6500K	100-265V	IP65	50,000Hrs	CE, RoHS, SGS, TUV, EMC
KL-S2000	100W	273*203.74	650g	80°	5000K	100-265V	IP65	50,000Hrs	CE, RoHS, SGS, TUV, EMC
KL-S2000	150W	347*214.5	650g	80°	6500K	100-265V	IP65	50,000Hrs	CE, RoHS, SGS, TUV, EMC
KL-S2000	150W	347*214.5	650g	80°	5000K	100-265V	IP65	50,000Hrs	CE, RoHS, SGS, TUV, EMC

## ADDITIONAL IMAGES



## Overview

### High-Performance Outdoor Illumination

The Gemini series 150W LED flood light is engineered for reliable and efficient outdoor lighting solutions. Designed for durability, this robust fixture provides uniform light distribution, making it an ideal choice for security lighting, landscape illumination, and general area coverage. Its high-quality construction ensures a long lifespan, meeting the demands of professional outdoor environments.

## Key Metrics

### Performance Highlights

**150 W**

Power Rating

**65 IP**

IP Rating

**80 CRI**

Color Rendering Index

## Technical Specifications

### Core Specifications

Parameter	Value
Input Voltage	100-265V
Luminous Flux	80/90 LM/W
Power Factor	0.9
Surge Protection	2KV
Color Temperature	2700-6500K

## Certifications

### Certifications & Standards

CE, ROHS, SGS, TUV, EMC

## Ordering & Logistics

### Series Model Data

Model	Power	Dimensions (cm)	PCS/CTN
RX-SZX030	30W	16x15x4	30
RX-SZX050	50W	20x19.5x4	16
RX-SZX100	100W	27.5x20.5x4	10
RX-SZX150	150W	34x26x4.5	8
RX-SZX200	200W	39x30x4.5	6