

2-Pole 25A Electronic AC Contactor for HVAC

This 2-pole contactor is designed for heating, air conditioning, refrigeration, data processing, and food service equipment. Silver Metal Oxide contacts guarantee dependable electrical performance over the product's life.



ADDITIONAL IMAGES



Overview

Reliable HVAC Switching

This 2-pole electronic AC contactor is engineered for consistent performance in HVAC, refrigeration, and heating systems. Designed for demanding electrical environments, it provides robust switching capabilities for inductive loads such as compressors, motors, and fans. Its compact footprint ensures seamless integration into control panels and equipment assemblies.

Electrical Ratings

Key Performance Metrics

25 A

Rated Current (FLA)

150 A

Locked Rotor Amps (LRA)

30 A

Resistive Load

Contact Ratings Per Pole

Voltage (VAC)	Horsepower (HP)
120	1.5
240	3
277	3

Technical Specifications

Physical and Coil Specs

- Configuration: 2 Poles
- Coil Voltage: 24-28 VAC/DC
- Terminal Torque: 25 in-lbs (2.8 Nm) Max

Certifications

CUL Certified

Ordering Information

Lead Time and Terms

- Delivery Time: 15-20 days after deposit
- Payment Terms: 30% deposit, balance against B/L copy