

2-Pole 30A 220V AC Magnetic Contactor

This 2-pole AC magnetic contactor is rated at 30A and 220V. It is suitable for a variety of electrical applications and operates at 50/60Hz.



Product Overview

Reliable 2-Pole AC Magnetic Contactor

This 2-pole AC magnetic contactor is designed for efficient power control in various industrial and commercial electrical applications. Rated for 30A and 220V operation, it supports a wide coil voltage range of 208-240VAC at 50/60Hz. Built for durability and safety, it features clearly labeled terminals and meets CE certification standards for international market compliance.

Key Performance Metrics

Key Performance Metrics

30 A

Rated Current

2

Number of Poles

220 V

Rated Voltage

Technical Specifications

Number of Poles	2
Electricity Type	AC
Coil Voltage	208-240VAC
Frequency	50/60Hz

Contact Ratings



Detailed view of the contactor housing featuring terminal markings (L1, L2, T1, T2) and comprehensive electrical rating data.

Contact Rating Per Pole

Voltage (VAC)	FLA (A)	LRA (A)	ERS (A)
240/277	30	240	40
480	30	200	40
600	30	180	40

Installation & Safety

Torque Requirements

- Standard Screws: 22 in-lbs
- Lugs: 40 in-lbs

Certifications

CE

Terminal Markings

L1, L2, T1, T2

Logistics

Shipping Ports

Ningbo, Shanghai