

# 2 Pole 30A HVAC Definite Purpose Contactor

This 2 pole, 30A definite purpose contactor is designed for HVAC and refrigeration applications. It is CUL certified, ensuring compliance with safety standards.



## ADDITIONAL IMAGES



## Overview

### Reliable HVAC Switching Solution

This 2-pole definite purpose contactor is engineered for demanding HVAC and refrigeration applications, providing reliable control for motors and compressors. It features a magnetic design for efficient switching and is CUL certified to meet rigorous safety standards. Designed for durability, it supports a wide range of voltages and is suitable for both inductive and resistive loads.

## Technical Specifications

### Rated Current

**30 A**

Full Load Amps (FLA)

**40 A**

Resistive Amps (RES)

Number of Poles	2
Coil Voltage	24 VAC
Frequency	50/60Hz

## Performance Ratings

### Contact Rating per Pole

Voltage (VAC)	FLA (A)	LRA (A)	RES (A)	Horsepower (HP)
120	30	180	40	2
240	30	150	40	3
277	30	120	40	5

## Installation & Compliance

### Wire Type

CU/AL • CLASS B

### Certifications

CUL, UL

### Terminal Torque

25 IN-LBS (2.8 NM)

## Service & Logistics

### Customization

Yes

### Lead Time

15-20 days after deposit

### Quality Control

100% self-inspection and testing before packing