

## 2-Pole 40A Contactor

This 2-pole, 40A contactor is designed for commercial applications requiring reliable switching. It is suitable for air conditioning, refrigeration, resistive heating, and lighting installations.



### ADDITIONAL IMAGES



### Product Overview

#### Reliable Switching for HVAC&R

This 2-pole, 40A contactor is engineered for demanding HVAC&R applications, providing efficient and safe electrical circuit control. Built with high-quality Silver Cadmium Oxide contacts, it ensures long-lasting performance in air conditioning systems. The unit features versatile termination options and robust thermal resistance, making it a dependable choice for compressor and fan motor circuits.

### Technical Specifications

#### Rated Current

**40 A**

Rated Current (FLA)

#### Pole Configuration

2 poles

#### Available Coil Voltages

24VAC, 120VAC, 240VAC, 277VAC, 380VAC, 480VAC

#### Operating Temperature

-40°F to +150°F / -40°C to +65°C

### Construction & Quality

#### Quality Assurance

- 100% self-inspection
- Pre-packing testing procedures

#### Contact Material

Silver Cadmium Oxide

## Logistics & Service

### Customization Options

OEM Available • ODM Available • Custom Logo Printing

### Standard Delivery Time

15-20 days after deposit

### Payment Terms

30% deposit, balance against B/L copy

### After-Sales Service

Replacement provided for quality issues