

## 2-Pole Contactor 20-30A

This 2-pole contactor is designed for commercial applications requiring reliable switching. It is suitable for air conditioning, refrigeration, resistive heating, lighting, and other installations.



### ADDITIONAL IMAGES



### Product Overview

#### High-Performance 2-Pole Contactor

This 2-pole contactor is engineered for demanding HVAC&R applications, providing reliable switching for air conditioning systems, compressor motors, and other high-power inductive loads. Featuring silver cadmium oxide contacts for durability, it ensures efficient and safe operation across a wide range of electrical environments. Designed for compatibility with various coil voltages, this contactor offers robust construction suitable for diverse industrial and residential cooling systems.

### Technical Specifications

Rated Current (FLA)	30 A
Poles	2-Pole
Coil Voltages	24VAC, 120VAC, 240VAC, 277VAC, 380VAC, 480VAC
Operating Temperature	-40°F to +150°F (-40°C to +65°C)
Termination Method	#10-32 Screw
Contact Material	Silver Cadmium Oxide

### Performance Data

#### Key Performance Ratings

**30 A**

Rated Current

**60 Hz**

Frequency

## Service & Support

### Service Terms

Policy	Details
Quality Assurance	100% self-inspection and testing before packing
After-Service	Replacement promised for quality defects
Lead Time	15-20 days after deposit
Payment Terms	30% deposit, balance against B/L copy