

# 210-Pint Industrial Dehumidifier with Pump

This industrial dehumidifier removes 210 pints of moisture per day at saturation. It has a built-in pump for continuous water drain out and operates between 35°F - 100°F.



## ADDITIONAL IMAGES



## Overview

### High-Capacity Industrial Moisture Control

This 210-pint industrial dehumidifier is engineered for demanding environments such as construction sites, water damage restoration, and large-scale industrial facilities. Featuring advanced LGR technology and a built-in water pump, it ensures continuous, unattended operation by automatically discharging collected moisture. Its rugged rotomolded housing and high airflow capacity make it a reliable solution for maintaining optimal humidity levels and preventing structural damage.

## Performance

Volts/Cycle	115V / 60 Hz
Water Removal Capacity	210 Pints/ Day at 90°F, 90% RH (Saturation) 175 Pints/ Day at 86°F, 80% RH 100 Pints/ Day at 80°F, 60% RH (AHAM)
Refrigerant	R410A / 26.5oz
Amps	10.2A (86°F, 80% RH)
Rated Airflow	220 CFM
Unit Weight (lbs)	115 lb (52kg)
Unit Dimensions (L x W x H)	24" x 21.5" x 39.4"
Packaging Weight (lbs)	128 lb (58kg)
Packaging Dimensions (L x W x H)	26.3" x 23.3" x 42.5"
Cord Length	20 ft
Housing	Rotomold (Plastic)
Stackable	No
Safety Certifications	ETL / CETL

Detailed technical parameters including water removal capacity, electrical ratings, and physical dimensions.

### Water Removal Capacity

**210 Pints/Day**

Saturation (90°F/90% RH)

**175 Pints/Day**

High Humidity (86°F/80% RH)

**100 Pints/Day**

AHAM Standard (80°F/60% RH)

**Rated Airflow**

220 CFM

**Temperature Operating Range**

35°F - 100°F

## Electrical & Refrigeration

Power Supply	AC 115V / 1PH / 60Hz
Rated Current	10.2 A
Refrigerant Type	R410A / 26.5oz
Power Cord Length	20 ft

## Physical Construction

Housing Material	Rotomold (Plastic)
Unit Dimensions (L x W x H)	24" x 21.5" x 39.4"
Unit Weight	115 lbs
Stackable Design	No

## Features & Compliance

### Key Features

- Built-in water pump for continuous drainage
- Continuous 24-hour operation capability
- LGR (Low Grain Refrigerant) technology
- Integrated condensate tank

Safety Certifications	ETL, CETL
Warranty Coverage	5-year warranty for Compressor & Condenser/Evaporator

## Logistics

### Shipping Details

Metric	Value
Packaging Dimensions	26.3" x 23.3" x 42.5"
Packaging Weight	128 lbs (58kg)