

3-Pole AC Magnetic Contactor

This 3-pole AC magnetic contactor is CUL certified and suitable for HVAC applications. It is designed for switching AC loads and ensures efficient operation in various systems.



ADDITIONAL IMAGES



Product Overview

Professional HVAC Magnetic Contactor

This 3-pole definite purpose magnetic contactor is engineered for reliable switching in heating, ventilation, and air conditioning systems. It is designed to handle demanding electrical loads in refrigeration compressors and motor applications, ensuring safe and efficient operation. With CUL certification, this component meets industry standards for durability and performance in professional HVAC environments.

Electrical Specifications

Rated Current

30 A

Rated Current

40 A

Resistive Load per Pole

Torque Specifications

Connection Type	Torque Range
Terminal Screws	10-20 lb. in.
Lug Set Screws	10-40 lb. in.

Coil Voltage	208/240VAC 50/60Hz
Number of Poles	3

Compliance & Standards

Certifications	CUL, UL E246810
Wire Compatibility	Cu 75°C

Service & Logistics

Frequently Asked Questions

- Samples available for testing (shipping cost excluded)
- OEM/ODM services available
- 100% self-inspection and testing before packing
- 15-20 days delivery time after deposit
- Payment terms: 30% deposit, balance against B/L copy