

30A 2-Pole Contactor for HVAC

This 2-pole, 30A contactor is designed for HVAC and refrigeration applications. It utilizes silver cadmium oxide contacts for reliable performance in demanding environments.



ADDITIONAL IMAGES



Product Overview

Professional Grade HVAC Contactor

This SA Series 2-pole contactor is engineered specifically for demanding HVAC and refrigeration applications. It provides reliable switching performance for compressors, motors, and other inductive loads across a wide voltage range. With robust construction designed for long-lasting operation, it is an essential component for air conditioning systems requiring consistent electrical control.

Electrical Specifications

Rated Current	30 A
Voltage Range	24V-480V
Number of Poles	2

Performance Metrics

Lifespan Rating

250000 cycles
Resistance Load Cycles

100000 cycles
Horsepower Load Cycles

1000000 cycles
Mechanical Life Cycles

Technical Details

Contact Ratings

VAC	HP	FLA	LRA	RES
120	1.5	16	96	30
208/240	3	12	72	30
277	3	9.6	58	30

Installation Parameters

- Torque Force: 25 LB-IN (2.8 Nm)
- Class B Insulation
- Compact design for tight spaces

Supply & Quality

Service Standards

Fast Delivery • Competitive Price • OEM/ODM Available • 18-year Experience