

3T Double Pump Low Profile Hydraulic Floor Jack

This 3T double pump low profile jack is designed for efficient lifting. Its double pump mechanism ensures quick lifting, while its low profile provides access to vehicles with minimal ground clearance.

SM-DH3 "Quick start" double pump technology
low location hydraulic floor jack

TECHNICAL PARAMETER

Capacity	3T
Min. height	75 mm
Max. height	505 mm
N.W.	32.2 kg
G.W.	34.2 kg
Quantity/20' CY	500PCS
Package Size	780*385*165MM

ADDITIONAL IMAGES



Product Overview

Professional 3T Low Profile Hydraulic Jack

This heavy-duty 3-ton hydraulic floor jack is engineered for professional automotive maintenance, featuring a low-profile design with a 75mm minimum height to access low-clearance vehicles. The 'Quick Start' double pump technology ensures rapid lifting to the contact point, significantly increasing operational efficiency. Built with a heavy-duty steel construction and integrated safety systems, it provides a stable and secure lifting solution for demanding workshop environments.

Performance Highlights

Lifting Performance

3 T

Lifting Capacity

75 mm

Minimum Height

505 mm

Maximum Height

Technical Features

Key Features

- Double pump 'Quick Start' technology for fast operation
- Heavy-duty steel construction for maximum stability
- Built-in safety valve to prevent overloading
- Hydraulic oil by-pass system to protect ram from over-extension
- Swivel saddle and rear casters for smooth maneuvering

Physical Specifications

Dimensions & Weight

Parameter	Value
Product Size	740 x 360 x 150 mm
Package Size	780 x 385 x 165 mm
Net Weight	32.2 kg
Gross Weight	34.2 kg

Quality & Logistics

Rigorous Testing

Key quality control points are established for every production line, with 100% testing conducted for all finished products. All sampled units are tested according to stringent national and international standards to ensure reliability in professional settings.

Container Capacity (20'CY)	500 PCS
----------------------------	---------