

3T x 2M Polyester Webbing Sling

This webbing sling is made from high-quality synthetic fiber using advanced weaving technology. It adheres to international standards, with a load range from 0.5t to 50t and safety factors of 4:1, 5:1, 6:1, 7:1, and 8:1, according to customer requirements.



ADDITIONAL IMAGES



Product Overview

High-Strength Polyester Webbing Sling

This 3-ton polyester webbing sling is engineered for professional lifting applications, offering a balance of high strength and flexibility. Constructed from 100% high-tenacity polyester with a double-ply layer, it ensures reliable performance and durability in demanding industrial environments. The sling features reinforced folded eyes and is designed to meet international safety standards for secure load handling.

Performance Metrics

Key Performance Metrics

3 t

Working Load Limit

6 :1

Safety Factor

75 mm

Webbing Width

Technical Specifications

Detailed Dimensions

Parameter	Value
Width	75mm
W.L.L.	3t
Safety Factor	6:1
Layer	Double ply
Material	100% high tenacity polyester
Construction	Double ply
Length	3 m
Lifting Eye Type	Folded Eye

Compliance & Standards

Standards Compliance

- EN1492 Standard
- Color coded according to EN standards

Certifications

CE • TUV Rheinland • GS • Geprüfte Sicherheit