

4000W Portable Inverter Generator

This portable inverter generator provides clean and reliable power for various applications. It features a 4000-watt starting capacity and a 3500-watt running capacity, making it suitable for powering sensitive electronics and appliances.

GENERATOR		4000W	
Starting System	Recoil / Electrical Starting		
Generator Material	Permanent magnets		
Frequency (Hz)	50Hz	60Hz	
Voltage(V)	250	120	
Rated Output (kW)	3.5	3.5	
Max. Output(kW)	3.8	3.6	
THD(%)	<3		
Running Time At 50% loading(h)	7	7	
Max Fuel Tank Capacity(L)	7.8		
Noise dB(A) 7m	57-71		
Insulation Grade	F		
ENGINE			
Model	M-225-2		
Engine Type	OHV, Air Cooling, 4 Stroke		
Displacement (cc)	224		
PACKING DETAILS			
Outside Packing Dimensions (mm)	725x420x530		
Net Weight (kg)	52		
Certifications	Euro V	CE	EPA CARB
Container load(20' GP/40' GP/40' HQ)	12/26/56		

ADDITIONAL IMAGES



Overview

Clean Power for Sensitive Electronics

This 4000W portable inverter generator is designed for both quiet operation and high-performance reliability. Featuring a compact, four-chamber silenced structure and THD <3% output, it delivers safe, stable electricity suitable for powering precision appliances like computers and televisions. With versatile starting options and parallel connection capabilities, it is an ideal power solution for camping, mobile shops, and outdoor activities.

Performance

Featured Metrics

4000 W

Starting Capacity

3500 W

Running Capacity

7 h

Run Time at 50% Load

7.8 L

Fuel Tank Capacity

Total Harmonic Distortion

< 3%

Engine & Technical

Engine Specifications

Feature	Specification
Engine Type	OHV, 4-stroke, Air-cooled
Displacement	224 cc
Starting System	Recoil and Electrical
Insulation Grade	F
Noise Level (at 7m)	71 dB(A)

Connectivity & Features

Available Outlets

- Multiple AC 120V Outlets
- DC 12V Outlet
- USB Port

Smart Features

Wireless Remote Start, Parallel Connection Capable, ECO Mode

Compliance & Logistics

Certifications

Euro V • CE • EPA • CARB

Physical Dimensions

Metric	Value
Dimensions (L x W x H)	705 x 420 x 630 mm
Net Weight	32 kg