

# 40A 1-Pole Contactor for HVAC

This definite purpose contactor is suitable for commercial applications including air conditioners, refrigeration, resistive heating, and lighting. It is designed to meet or exceed electrical and mechanical requirements as defined by Definite Purpose Contactors standard of USA/Canada.



## ADDITIONAL IMAGES



## Product Overview

### High-Performance Definite Purpose Contactor

This 1-pole contactor is engineered for demanding commercial HVAC and refrigeration applications, including air conditioning systems, resistive heating, and lighting installations. Designed to meet rigorous electrical and mechanical standards, it provides a reliable, cost-effective solution for switching electrical circuits. The unit features durable silver cadmium oxide contacts and is built to withstand extreme temperature environments.

## Electrical Ratings

### Rated Current

**40 A**

Full Load Amps (FLA)

### Available Coil Voltages

- 24
- 120
- 240
- 277
- 380
- 480

## Design & Construction

Pole Configuration	1-Pole
Contact Material	Silver Cadmium Oxide
Termination Method	Box Lug

## Operating Environment

Operating Temperature Range	-40°F to +150°F (-40°C to +65°C)
-----------------------------	----------------------------------

## Certifications & Compliance

Standards Compliance	USA Standard, Canada Standard
----------------------	-------------------------------

## Ordering & Support

### Service & Ordering Terms

Category	Details
Lead Time	15-20 days after deposit
Payment Terms	30% deposit, balance against B/L copy
Customization	OEM/ODM available
Quality Assurance	100% self-inspection and testing