

5-Ton Telescopic Handler

This telescopic handler is capable of lifting loads up to 5 tons. Its telescopic boom provides extended reach for material handling, construction, and maintenance tasks.



Overview

Heavy-Duty Telescopic Handler

This 5-ton telescopic handler is engineered for demanding construction and industrial material handling tasks. It features a robust chassis and a high-reach telescopic boom, providing exceptional versatility for site operations. Designed with operator safety and efficiency in mind, this machine offers reliable performance in challenging environments.

Performance Metrics

Lifting Capacity

5000 kg
Max Capacity

8800 mm
Max Lifting Height

5470 mm
Max Horizontal Reach

Operational Capabilities

- Operating weight: 13000 kg
- Max Gradeability: e20%
- Max Traveling Speed: 25 Km/h
- Min Turning Radius: 6800 mm

Boom Articulation

Horizontal Tip angle of big arm: 60°-12°

Dimensions

Machine Dimensions

Dimension	Value	Unit
Overall Length (without fork)	5900	mm
Overall Width	2350	mm
Overall Height	2655	mm
Cab Height	2400	mm
Min. Ground Clearance	310	mm

Wheel and Axle Specifications

- Wheel Base: 2988 mm
- Front Wheel Tread: 1638 mm
- Rear Wheel Tread: 1845 mm
- Rear Overhand Length: 1055 mm
- Front Tire Size: 11.00-20
- Rear Tire Size: 9.00-20