

5000W Gasoline Generator with Electric Start

This gasoline generator delivers 5000W of running power and 5500W of peak power. It includes AC outlets for connecting standard electrical devices and a rechargeable sealed lead-acid battery for reliable electric starting.

PRODUCT PARAMETERS

Engine type	Single cylinder, 4-Stroke(OHV)
Starting system	Recoil/Electric starter
Displacement	389ml
Bore x Stroke	88x64mm
Compression ratio	8.5:1
Rated frequency	50Hz/60Hz
Rated voltage	230V/120V/240V
Rated power	5000W
Max. power	5.5kW(5.2kW)
DC output	12V / 8.3A
Fuel tank capacity	25L
Full load continuous running time	8h/7h
1/2 load continuous running time	12h/11h
Noise (FM)	72dB(A)@1m
Dimensions(L*W*H)	685x440x442mm
Net weight	85kg

ADDITIONAL IMAGES



Overview

Reliable Power Solution

This high-performance gasoline generator is engineered with a robust 4-stroke OHV engine, delivering reliable power for a variety of professional and residential applications. With a 5000W running capacity and a large 25L fuel tank, it ensures extended operation times for critical needs. Designed for convenience, the unit features both recoil and electric starting systems, making it accessible and easy to operate in any environment.

Performance Metrics

Power Output

5000 W
Running Power

5500 W
Peak Power

Runtime Performance

Load Type	Runtime (50Hz)	Runtime (60Hz)
Full Load	8h	7h
1/2 Load	12h	11h

Engine Specifications

Engine Specifications

- Single cylinder, 4-Stroke (OHV)
- Displacement: 389ml
- Bore x Stroke: 88x64mm
- Compression Ratio: 8.5:1
- Recoil/Electric starter system

Electrical Specifications

Electrical Output

- Rated Frequency: 50Hz/60Hz
- Rated Voltage: 230V/120V/240V
- DC Output: 12V/8.3A

Physical Characteristics

Physical Dimensions & Weight

85 kg

Net Weight

72 dB

Noise Level (50Hz)

Dimensions (L x W x H)

683 x 540 x 542 mm

Features

Key Features

Electric Start, Recoil Start, Portable Frame, Wheeled Design, Sealed Lead-Acid Battery