

60A 3-Phase AC Definite Purpose Contactor

This 3-phase AC contactor is rated for 60A and utilizes a magnetic mechanism. It offers flexibility and convenient wire connection through quick connect terminals, screws, or box lugs.



ADDITIONAL IMAGES



Overview

High-Performance HVAC Contactor

This 3-phase definite purpose contactor is engineered for reliable switching in heating, ventilation, air conditioning, and refrigeration systems. Featuring a robust 60A current rating and a 3-pole configuration, it provides consistent electrical control for hermetic refrigeration compressors and other HVAC equipment. Designed for durability and ease of installation, this unit supports a wide range of voltage requirements to suit diverse operational environments.

Electrical Ratings

Key Performance Metrics

60 A

Full Load Amps (FLA)

3 P

Poles

208 VAC

Coil Voltage

Horsepower Ratings

Configuration	Rating
1-Phase	5 HP
3-Phase (240V)	10 HP
3-Phase (480/600V)	20-30 HP

Voltage Compatibility

120VAC, 240VAC, 480VAC, 600VAC

Installation & Compliance

Torque Specifications

- Power terminal screw: 20 lb. in.
- Lug set screw: 40 lb. in.

Certifications

CE • UL Listed

Wire Compatibility

Cu 75°C wire