

8-Ton Rough Terrain Crane with Auger Attachment

This 8-ton crane is designed for rough terrain and agricultural construction. It features a crane arm and auger attachment for versatile lifting and drilling operations.



Overview

8 Ton Tractor Crane	
Model	HT8000
Capacity	8000kg
Max. Height	22m
Max. Torque	4200 Nm
Max. Angle	±350°
Max. Speed	15km/h
Max. Fuel	100L
Max. Power	100kW
Max. Weight	10000kg
Max. Length	10m
Max. Width	2.5m
Max. Depth	1.5m
Max. Clearance	1.5m
Max. Tilt	±5°
Max. Slope	±10%
Max. Wind	10m/s
Max. Rain	50mm/h
Max. Temp	0-40°C
Max. Humidity	80%
Max. Vibration	0.5g
Max. Shock	0.5g
Max. Seismic	0.2g
Max. Noise	85dB(A)
Max. Emission	Stage II
Max. Safety	ISO 9001
Max. Warranty	3 Years
Max. Service	24/7
Max. Support	Global

A versatile 8-ton tractor-based crane designed for rough terrain, lifting, and drilling applications.

8-Ton Rough Terrain Crane

This high-performance 8-ton rough terrain crane is engineered for versatility and efficiency in challenging agricultural and construction environments. It features a robust 4-wheel drive tractor base that ensures superior maneuverability on uneven ground, combined with a powerful auger attachment for precise drilling operations. With an optimized hydraulic system that reduces oil consumption, this crane offers both high operational stability and long-term cost-saving benefits.

Core Specifications

Key Performance Metrics

8 t

Max Lifting Capacity

22 m

Max Lifting Height

20 T.M

Max Lifting Moment

Operational Details

Feature	Value
Rotation Angle	<350°
Boom Type	Dual telescopic cylinder (5 sections)
Angle Range	-15° to -75°
Outrigger Legs	5
Drilling Torque	4200 N.M

Certifications

Compliance & Certifications

GS, SGS, CE, ISO9001

Physical Dimensions

Machine Dimensions

- Overall Size: 6152 x 3455 x 2100 mm
- Wheelbase: 2580 mm
- Minimum Clearance: 460 mm
- Curb Weight: 9500 kg