

80mm Thermal Receipt Printer with Multiple Interfaces

This 80mm thermal receipt printer is compatible with EPSON ESC/POS and STAR Line mode command sets. It supports a 250mm/sec print speed and offers multiple interfaces including Serial, USB, and Ethernet.



ADDITIONAL IMAGES



Product Overview

High-Speed Thermal Receipt Printing

This 80mm thermal receipt printer is engineered for high-speed, reliable performance in demanding retail and hospitality environments. It features an easy paper loading mechanism, a durable cutter, and versatile interface options for seamless POS system integration. Designed for efficiency, it supports various character sets and configurable settings to meet diverse business requirements.

Technical Specifications

Baud Rate Options

- 9600
- 19200
- 38400
- 115200

Print Width	80 mm
-------------	-------

Configurable Characters per Line	42, 48
----------------------------------	--------

Configuration & Settings

DIP Switch Configuration Table

Switch	Function	Option 1	Option 2
SW-1	Select cutter	No	Yes
SW-2	Select beeper	Yes	No
SW-3	Select print density	Dark	Light
SW-4	Two-byte character code	No	Yes
SW-5	Character per line	42	48
SW-6	DK(RJ11) port output	Yes	No

Language & Character Support

Supported Character Sets

Alphanumeric • Katakana • Multilingual • Portuguese • Canadian • West Europe • Hebrew • Iran • East Europe • Latin • Latvian