

9V Zinc Carbon Dry Cell Battery


This 9V zinc carbon dry cell battery is designed for general-purpose applications. Its extra heavy-duty construction ensures a reliable power source for low-drain devices.



ADDITIONAL IMAGES



Overview



Overview of available battery models and construction types.

Reliable 9V Power Solution

This 9V extra heavy-duty zinc-carbon dry cell battery is engineered for consistent performance in low-drain household and business electronics. Featuring a durable aluminum foil jacket and leak-proof design, it provides a stable voltage output suitable for devices like smoke detectors and toys. With a 3-year shelf life and mercury-free composition, it offers an environmentally conscious and long-lasting energy option.

Technical Specifications

Durata Size 9V
Durata 9V batteries are built with PowerLock Technology for a long lasting performance. They have a 3-year shelf life and are perfectly compatible with most household and business devices. They are commonly used in power smoke detectors and remote controls.

SPECIFICATIONS		NO MODEL KEY
Type	9V F22 R6P	
Model	6F22 (006P)	
Capacity	500mAh	
Material	Aluminum Foil Jacket	
Technology	PowerLock Technology	
Shelf Life	3 years	
Material	Aluminum	
Dimensions	50.5mm x 26.5mm x 50.5mm	
Weight	45g	
Applications	Smoke Detectors, Remote Controls, Security Systems, etc.	
Service Life	2700mAh @ 5.4V (I/d)	11 hours
Product	1100mAh	7 hours



Model	Capacity	Weight	Dimensions
6F22 (006P)	500mAh	45g	50.5mm x 26.5mm x 50.5mm
6F22 (006P)	500mAh	45g	50.5mm x 26.5mm x 50.5mm
6F22 (006P)	500mAh	45g	50.5mm x 26.5mm x 50.5mm
6F22 (006P)	500mAh	45g	50.5mm x 26.5mm x 50.5mm

Detailed technical specifications and packaging configuration for the 9V battery.

Nominal Voltage	9 V
Battery Type	6F22 (006P)
Battery Class	Extra Heavy Duty
Shelf Life	3 years
Exterior Material	Aluminum Foil Jacket

Performance Metrics

Service Life (IEC Standard)

7 hours


IEC Standard Discharge

Service Life (Standard Conditions)

11 hours

Standard Discharge (2700mAh, I/d, EV 5.4V)

Compliance & Safety



International certifications and quality standards compliance.

Certifications

IEC • ISO 9001 • ISO 14001 • ISO 45001 • RoHS • CE • UL

Safety Features

Mercury-free, Leak-proof, Anti-corrosion

Logistics & Packaging

Packaging Specifications

Item	Details
Consumer Package	1 Battery / Shrink Pack
Inner Box	12 Batteries
Outer Carton	480 Batteries (40 Boxes)
Carton Dimensions	270 x 240 x 250 mm
Gross Weight / Carton	18.5 kg

Shipping & Trade Terms

- Trade Terms: CFR
- Transportation: Sea freight
- Lead Time: Approx. 35 days after advance payment
- Payment: L/C at sight or T/T (50% deposit)