

# AAA Zinc Carbon Battery 1.5V

This AAA size battery provides 1.5V of power. It utilizes zinc-carbon technology for general use in various electronic devices.



## ADDITIONAL IMAGES



## Product Overview



Extra heavy-duty AAA battery designed for reliable, long-lasting power.

### High-Performance Zinc Chloride Battery


This AAA-sized 1.5V dry cell battery is engineered for extra heavy-duty performance, providing a reliable power solution for a wide range of household and professional devices. Built with advanced leak-proof and heat-proof technology, it ensures durability and safety even in challenging conditions. With a 4-year shelf life and mercury-free composition, this battery offers an efficient, environmentally conscious, and cost-effective power source for your electronics.

## Technical Specifications

**DurataPlus Size AAA**

DurataPlus Size AAA 1.5V batteries are built with Proseal Lock Technology for a strong leak-proof performance. They have a longer shelf life and are packaged in a durable leak-proof shrink pack and shrink card, including alkaline zinc-carbon correct type, long-life, correct, correct, correct and long life.

SPECIFICATION		FIGURE
Type	AAA (R03)	FIGURE 1
Size	20.5 x 26.2 x 44.5 mm (L x W x H)	FIGURE 2
Capacity	1000 mAh (20°C, 25°C, 30°C)	FIGURE 3
Self-Discharge	10% per year	FIGURE 4
Shelf Life	4 Years	FIGURE 5
Material	Alkaline	FIGURE 6
Temperature	-20°C to 60°C	FIGURE 7
Operating	100, 1000, 10000, 100000, 1000000	FIGURE 8
Compliance	IEC 60086-2, IEC 60086-3, IEC 60086-4, IEC 60086-5, IEC 60086-6, IEC 60086-7, IEC 60086-8, IEC 60086-9, IEC 60086-10, IEC 60086-11, IEC 60086-12, IEC 60086-13, IEC 60086-14, IEC 60086-15, IEC 60086-16, IEC 60086-17, IEC 60086-18, IEC 60086-19, IEC 60086-20, IEC 60086-21, IEC 60086-22, IEC 60086-23, IEC 60086-24, IEC 60086-25, IEC 60086-26, IEC 60086-27, IEC 60086-28, IEC 60086-29, IEC 60086-30, IEC 60086-31, IEC 60086-32, IEC 60086-33, IEC 60086-34, IEC 60086-35, IEC 60086-36, IEC 60086-37, IEC 60086-38, IEC 60086-39, IEC 60086-40, IEC 60086-41, IEC 60086-42, IEC 60086-43, IEC 60086-44, IEC 60086-45, IEC 60086-46, IEC 60086-47, IEC 60086-48, IEC 60086-49, IEC 60086-50, IEC 60086-51, IEC 60086-52, IEC 60086-53, IEC 60086-54, IEC 60086-55, IEC 60086-56, IEC 60086-57, IEC 60086-58, IEC 60086-59, IEC 60086-60, IEC 60086-61, IEC 60086-62, IEC 60086-63, IEC 60086-64, IEC 60086-65, IEC 60086-66, IEC 60086-67, IEC 60086-68, IEC 60086-69, IEC 60086-70, IEC 60086-71, IEC 60086-72, IEC 60086-73, IEC 60086-74, IEC 60086-75, IEC 60086-76, IEC 60086-77, IEC 60086-78, IEC 60086-79, IEC 60086-80, IEC 60086-81, IEC 60086-82, IEC 60086-83, IEC 60086-84, IEC 60086-85, IEC 60086-86, IEC 60086-87, IEC 60086-88, IEC 60086-89, IEC 60086-90, IEC 60086-91, IEC 60086-92, IEC 60086-93, IEC 60086-94, IEC 60086-95, IEC 60086-96, IEC 60086-97, IEC 60086-98, IEC 60086-99, IEC 60086-100	FIGURE 9



Detailed technical specifications and performance data for the AAA zinc chloride battery.

## Technical Details

Attribute	Value
Battery Size	AAA (R03)
Nominal Voltage	1.5V
Chemistry	Zinc Chloride
Shelf Life	4 Years
HS Code	850610

## Performance & Safety



**Brand Vision**

DurataPlus Size AAA 1.5V batteries are built with Proseal Lock Technology for a strong leak-proof performance. They have a longer shelf life and are packaged in a durable leak-proof shrink pack and shrink card, including alkaline zinc-carbon correct type, long-life, correct, correct, correct and long life.

Type	Capacity (mAh)	Self-Discharge (%)	Shelf Life (Years)
AAA (R03)	1000	10%	4
AA (R06)	1800	10%	4
A (R09)	2400	10%	4
C (R14)	5000	10%	4
D (R20)	12000	10%	4

Performance comparison and safety certifications highlight leak-proof and heat-proof design.

## Performance Highlights

**160 %**

Performance vs Standard

**50 °C**

Heat Resistance Limit

## Safety Features

Leak-Proof, Heat-Proof, 0% Mercury, 0% Cadmium

## Logistics & Packaging

### Packaging Options

- Shrink pack
- Shrink card
- Box
- Carton

### Carton Specifications

Metric	Value
Carton Dimensions	363 x 240 x 168 mm
Batteries per Carton	1800
Gross Weight	14.5 kg

## Compliance



Global certifications and quality assurance compliance standards.

### Certifications & Standards

IEC • ISO 9001 • ISO 14001 • RoHS Compliant • CE • UL