

AC Contactor up to 95A 660V

This AC contactor is suitable for use in circuits up to the rated voltage 660V AC 50Hz or 60Hz. With a rated current up to 95A, it is designed for making, breaking, frequently starting, and machine interlocking.



ADDITIONAL IMAGES



Product Overview

High-Performance AC Contactor

The CJX2 series AC contactor is engineered for reliable long-distance circuit connection and disconnection, making it ideal for frequent starting and control of AC motors. Designed for versatility, this unit supports 3-phase systems and can be easily expanded with auxiliary contact blocks, air delay heads, or mechanical interlocking mechanisms. It conforms to international standards, ensuring consistent performance in demanding industrial environments.

Technical Specifications

Rated Current	95 A
Max Rated Voltage	690 V
Operating Frequency	50/60 Hz
Configuration	3 Pole, 3 Phase

Performance Metrics

Service Life

100000 Cycles

Electrical Life

1000000 Cycles

Mechanical Life

Compliance & Quality

Certifications

CE • CUL • IEC60947 • GB14048.4

Construction Material

Thermoplastic

Compatibility

Coil Voltage Options

- 24
- 36
- 42
- 48
- 110
- 127
- 220
- 230
- 240
- 380
- 400
- 415
- 440
- 480
- 600