

# Adjustable Industrial Blower Fan

This adjustable blower fan is designed for industrial and commercial applications requiring high-volume air movement. The blower features a robust construction with a durable metal housing and adjustable stand for precise airflow positioning.

性能參數表 Technical Data Sheet

型號	規格	風量	轉速	功率	噪音	風壓	風速	重量	淨重
Model	Size(mm)	(m³/h)	Phase	(W)	(dB)	(Pa)	(m/s)	Capacity (m³/min)	Net Wt (kg)
SHT-20	200mm	200	1	500	250	2800/3300	25	245	6.5
SHT-25	250mm	250	1	500	300	2800/3300	43	244	6.5
SHT-30	300mm	300	1	500	320	2800/3300	55	270	11
SHT-35	350mm	350	1	500	350	2800/3300	62	268	10
SHT-40	400mm	400	1	500	400	2800/3300	75	295	14
SHT-50	500mm	500	1	500	350	2800/3300	65	244	6.5
SHT-60	600mm	600	1	500	350	2800/3300	62	268	10
SHT-80	800mm	800	1	500	350	2800/3300	62	268	10
SHT-100	1000mm	1000	1	500	350	2800/3300	62	268	10
SHT-120	1200mm	1200	1	500	350	2800/3300	62	268	10
SHT-150	1500mm	1500	1	500	350	2800/3300	62	268	10
SHT-180	1800mm	1800	1	500	350	2800/3300	62	268	10
SHT-200	2000mm	2000	1	500	350	2800/3300	62	268	10
SHT-250	2500mm	2500	1	500	350	2800/3300	62	268	10
SHT-300	3000mm	3000	1	500	350	2800/3300	62	268	10
SHT-350	3500mm	3500	1	500	350	2800/3300	62	268	10
SHT-400	4000mm	4000	1	500	350	2800/3300	62	268	10
SHT-450	4500mm	4500	1	500	350	2800/3300	62	268	10
SHT-500	5000mm	5000	1	500	350	2800/3300	62	268	10
SHT-600	6000mm	6000	1	500	350	2800/3300	62	268	10
SHT-700	7000mm	7000	1	500	350	2800/3300	62	268	10
SHT-800	8000mm	8000	1	500	350	2800/3300	62	268	10
SHT-900	9000mm	9000	1	500	350	2800/3300	62	268	10
SHT-1000	10000mm	10000	1	500	350	2800/3300	62	268	10

## ADDITIONAL IMAGES



## Product Overview

### High-Performance Industrial Ventilation

This adjustable industrial blower fan is designed for professional environments requiring reliable supply and exhaust ventilation. It features a robust metal housing with a powder-coated finish for corrosion resistance and an integrated handle for easy portability. Ideal for long-distance air movement in ship building, municipal engineering, and chemical facilities, it combines high wind pressure with a stable, safe design.

## Design & Portability

### Design Features

Adjustable Stand, Built-in Handle, Portable Design, Powder-Coated Finish, One-Piece Safety Switch

## Safety & Construction

### Safety Protections

- Protective grill to prevent blade contact
- Thermal overload motor protection
- Durable metal housing
- Stable capacity design

## Performance Range

### Key Performance Metrics

**200 mm**

Minimum Diameter

**600 mm**

Maximum Diameter

**3300 r/min**

Max Rotation Speed

## Technical Specifications

### Technical Data Sheet

Model	Size (mm)	Power (W)	Capacity (m <sup>3</sup> /min)	Static Pressure (Pa)	Noise (dB(A))
SHT-20	200	230	25	245	60
SHT-25	250	320	43	294	68
SHT-30	300	520	65	370	78
SHT-35	350	750	82	598	80
SHT-40	400	1100	96	700	80
SHT-50	500	2000	200	1050	88
SHT-60	600	2200	240	1100	92

## Applications

### Primary Applications

- Communication cable maintenance
- Ship building and repairing
- Municipal underground engineering
- Chemical industrial factories
- Large capacity tank containers

## Electrical Requirements

### Available Voltages

110V • 220V • 380V