

Adjustable Pipe Dismantling Joint

The dismantling joint provides longitudinal adjustment, facilitating easy installation of flanged equipment. It accommodates expansion and contraction in pipeline systems, simplifying maintenance.



ADDITIONAL IMAGES



Product Overview

Versatile Pipeline Solution

This adjustable dismantling joint is engineered to provide longitudinal adjustment, facilitating the seamless installation and removal of flanged equipment such as valves and pumps. Designed to accommodate expansion, contraction, and settlement, it effectively simplifies maintenance procedures and reduces system downtime. Its robust construction ensures reliable, leak-free performance across demanding industrial environments including water treatment, power generation, and chemical processing.

Design Standards

Flange Compatibility

- DIN PN10/16/25
- ANSI B16.1
- BS4504
- ISO PN10/16
- JIS B2212/2213
- BS 10 Table D
- BS 10 Table E

Face-to-Face Standard

- API 609
- ISO 5752 series 20
- BS 5155

Compliance Standards

MSS SP-67, API 609, EN 593

Top Flange Standard

ISO 5211

Performance & Certification

Certifications

ISO 9001:2000 • CE • UL • RoHS

Testing Standard

API 598

Key Features

Design Advantages

- Expanded joint formation for bending connection valves
- Reliable sealing with zero leakage
- Easy installation and dismantling process
- Material versatility to suit various media