

Airless Paint Sprayer with Diaphragm Pump

This airless paint sprayer features a diaphragm pump for efficient and consistent paint application. It is designed for various coating projects, delivering a smooth and professional finish.



www.merhein.com

Overview

Professional Grade Airless Sprayer

This portable airless paint sprayer features a robust diaphragm pump design, engineered for consistent and efficient coating applications. Built for mobility, the unit includes a convenient hand-carrying frame with skid-mount feet, making it easy to transport between job sites or up stairs. Equipped with a reliable TEFC induction motor and a precision mechanical pressure control valve, it delivers professional-grade performance for a wide range of coatings from stains to emulsion paints.

Performance Metrics

Key Performance Metrics

2.1 L/min

Max Flow Rate

210 Bar

Max Pressure

1100 W

Motor Power

Technical Specifications

Power Requirements	110/220V, 50/60Hz
Nozzle Specifications	0.017" (Suggested), 0.019" (Max)
Optimal Spraying Distance	350-400mm
Hydraulic Oil Type	ISO VG32

Compliance & Quality

Certifications	EMC, LVD, MD, RoHS, GS
----------------	------------------------

Logistics

Dimensions & Weight

Metric	Value
Packing Size	44 x 37 x 51 cm
Net Weight	25 kg
Gross Weight	27 kg

Standard Accessories

Included Components

- 15m pressure hose
- 45cm extension wand
- Spray gun with 517 tip
- Hand tool kit
- Suction tube
- Easy wearing spare parts
- Pressure gauge
- 5L plastic hopper
- English manual