

American Standard Alloy Steel D Shackle

This D shackle is made from high-strength alloy steel, ensuring strength and resistance to deformation under heavy loads. It is suitable for rigging, lifting, and towing applications, and finished with a galvanized coating for corrosion protection.



ADDITIONAL IMAGES



Product Overview

High-Strength D Shackle

This American Standard D Shackle (G2150) is a robust lifting component engineered for heavy-duty industrial applications. Constructed from high-strength alloy steel, this shackle offers exceptional durability and resistance to deformation under load. It features a screw pin closure for secure and easy attachment, finished with a galvanized coating to protect against corrosion and extend its service life in demanding rigging, lifting, and towing environments.

Compliance & Standards

CE • CCC • GS • ISO 9001 • OHSAS 18001 • ISO 14001

Technical Specifications

Dimensions & WLL Table

Size (in)	W.L.L (t)	Weight (lbs)
1/4	1/2	0.13
5/16	3/4	0.23
3/8	1	0.33
7/16	1-1/2	0.49
1/2	2	0.75
5/8	3-1/4	1.47
3/4	4-3/4	2.52
7/8	6-1/2	3.85
1	8-1/2	5.55
1-1/8	9-1/2	7.60
1-1/4	12	10.81
1-3/8	13-1/2	13.75
1-1/2	17	18.50
1-3/4	25	31.40
2	35	46.75
2-1/2	55	85.00

Material	Alloy Steel
Shackle Type	D Shackle (G2150)