

Anchor Handling Tug Supply Vessel with DP2

This anchor handling tug supply vessel has a length overall of 58.7m and is equipped with a DP2 dynamic positioning system. It is designed to support offshore operations with a spacious deck for cargo and specialized winches for anchor handling and towing.



ADDITIONAL IMAGES



Overview

High-Performance Offshore Support

This Anchor Handling Tug Supply Vessel (AHTS) is engineered for demanding offshore operations, featuring advanced DP2 dynamic positioning for superior maneuverability. With a robust bollard pull of 60 tonnes and powerful propulsion, it is built to handle complex towing and anchor handling tasks in harsh marine environments. The vessel combines efficient cargo capacity with essential firefighting capabilities, ensuring reliability and safety for oil and gas industry support.

Dimensions

Technical Dimensions

Parameter	Value
Length Overall	58.7 m
Length B.P.	53.2 m
Breadth Moulded	14.6 m
Depth Moulded	5.5 m
Draft Moulded	4.75 m

Performance & Propulsion

Key Performance Metrics

13.5 Knots

Max Speed

60 Tonnes

Bollard Pull

Propulsion System

Controllable Pitch Propeller

Main Engine Power

2 x 2575 BHP

Capacities & Equipment

Tank Capacities

- Fuel Oil: 475 m3
- Fresh Water: 235 m3

Safety & Firefighting

Fi-Fi 1 • FFS Equipment • DP2 System