

AS/NZ 3112 Plug to IEC 60320 C15 Power Cord

This power cord features an Australian AS/NZ 3112 standard plug on one end and an IEC 60320 C15 connector on the other. It is designed for connecting devices to a power source in Australia and New Zealand and is typically used for equipment requiring a higher temperature rating than the C13 connector can provide.



Product Overview

High-Performance Power Connectivity

This power cord features a standard Australian AS/NZ 3112 three-prong plug on one end and an IEC 60320 C15 connector on the other, specifically engineered for the Australian and New Zealand markets. The C15 connector is designed for equipment requiring higher temperature ratings, making it ideal for professional computing and networking hardware. Built to rigorous standards, this cable ensures reliable power delivery with full safety certifications for peace of mind.

Technical Specifications

Connector Types

End	Type
Plug	AS/NZ 3112 (3-prong)
Connector	IEC 60320 C15

Compatible Cable Types

- H03VV-F 3G0.5-0.75 mm²
- H05VV-F 3G0.75-2.5 mm²
- H03RT-F 3G0.75-1.0 mm²
- H05RR-F 3G0.75-1.5 mm²
- H05RN-F 3G0.75-1.0 mm²
- H07RR-F 3G0.75-1.0-1.5 mm²

Maximum Voltage	250 V
-----------------	-------

Compliance & Logistics

Certifications	SAA, RoHS, REACH
Minimum Order Quantity	2000